Data sheet LED200WFB

LED200WFB

2x 10W LED Wi-Fi PIR Twin Floodlight - Black

Features & Benefits

- Hi-Lo dimming. Floodlight remains on at a dimmed level and illuminates to full brightness when PIR detects movement. Reverts back to dimmed level when detected movement ends. Permanent On & Off modes via app.
- Remote adjustments for the lux, time delay, Hi-Lo dimming, brightness, motion and colour temperature settings direct from the Tuya Smart App.
- Indirect Load Activation: Other compatible Tuya Smart devices can be triggered when the PIR picks up someone in the detection area.
- Simple, snap in wall plate with fast-fix pin terminal block for quick and easy installation.
- Independent Pan & Tilt light aiming adjustment
- Sleek cooling fin design to prevent intense heat build-up



| Operating Voltage | 230V AC |
|------------------------------|------------------|
| Frequency | 50Hz |
| Installation Type | Surface Mount |
| Earth Class Rating | Class II |
| Operating Temperature | -20°C to 50°C |
| Ingress Protection Rating | IP55 |
| Setting Type | WIFI (App Based) |
| Approved Mounting Height (m) | 2.5 |



Subject to technical changes and revisions

additional information at: https://www.timeguard.com This data was generated on

Data sheet LED200WFB

| Motion Detection (m) | 10 |
|----------------------------|--|
| Detection Angle | 140° |
| PIR Sensitivity | (Adjustable) App Based |
| VPN Support | No |
| Program Modes | 24 Hour/7 Day, Manual Override, Hi-Lo Dimming (2nd Stage Lighting), Lux & Time ON Adjustments, Motion Detction Sensitivity, Colour Temperature Adjustments. |
| Wattage | 20 |
| Beam Angle | 120° |
| Pan & Tilt Adjustment | 80° Tilt Downwards, 35° Pan Left/Right (From Centre) |
| Energy Efficiency | Class F |
| Energy Usage | 20KwH/1000H |
| Lumen Output (Im) | 2000 |
| Luminaire Efficiency | 100 lm/W |
| Colour Temperature (K) | 3000 - 6500 |
| LED Type | SMD (Integrated) |
| Mounting Hole Centres (mm) | 84 |
| Standby Consumption | <0.5W |
| ON Time Adjustment | 5 Seconds - 60 Minutes |
| LUX Level | 10 - 1000 |
| Detection Range (m) | 10 |
| Permanent ON Facility | Yes (App Enabled) |
| Dusk Till Dawn | Yes (App Enabled) |
| Multiple Unit Support | Yes (Multiple Devices On App) |
| Cable Capacity (mm2) | 2.5mm2 |
| Cable Entry(s) | Back Entry, Bottom Entry, Top Entry |
| | |



additional information at: https://www.timeguard.com This data was generated on

Data sheet LED200WFB

General

| Weight (g) | 448 |
|-----------------------------|------------------------------------|
| Height (mm) | 205 |
| Width (mm) | 195 |
| Depth (mm) | 78 |
| Body Construction | Polycarbonate |
| Product Colour | Black |
| Accessories (Included) | Rawl Plugs, Screws, Corner Bracket |
| EAN Number | 5012483015964 |
| Guarantee Period | 3 Years |
| Trade Tariff Commodity Code | 9405114090 |

Line Diagrams





