

NTM01

24 Hour Compact Segment Module

Features & Benefits

- ‘Traffic Light’ Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Easy to Use Captive Segment Dial
- Permanent ON/OFF control



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	OEM (Panel Mount)
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Setting Type	Segment
Program Modes	24 Hour
Voltage Free Contacts	Normally Open, Normally Closed (Changeover)
Mounting Hole Centres (mm)	54
Standby Consumption	<1.43W
Number of Channels	1
Switch rating	16A Resistive, 8A Inductive, 1HP Motor, 750W Halogen/Flurescent, 100W CFL, 100W LED
Shortest Switching Time	15 Minute

Data sheet

NTM01

Time / OEM Modules

Programmable Slots	48 ON 48 OFF (98 Segments)
Permanent ON Facility	Yes (Slider Switch)
Cable Entry(s)	Bottom Entry (Spade Connector)

General

Weight (g)	73
Height (mm)	60
Width (mm)	60
Depth (mm)	36
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483012208
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032890090

Line Diagrams

