

NTT01

24 Hour Compact Immersion Heater Timeswitch

Features & Benefits

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED 'Mains ON' and Green LED 'Output' Indicators For Easy Viewing
- 'Traffic Light' Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Switches ON and OFF at Preset Times
- Easy to Use Captive Segment Dial
- Permanent ON/OFF Control
- Fits a Standard Flush or Surface Mount Box min 32mm



Technical Data

| | |
|-----------------------------|---------------|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Surface Mount |
| Earth Class Rating | Class II |
| Operating Temperature | 0°C to 40°C |
| Ingress Protection Rating | IP20 |
| Setting Type | Segment |
| Back Box Minimum Depth (mm) | 32 |
| Program Modes | 24 Hour |
| Mounting Hole Centres (mm) | 60 |
| Standby Consumption | <1.43W |

Data sheet

NTT01

Time / Immersion & General Purpose Timeswitches

| | |
|-------------------------|--------------------------------------|
| Number of Channels | 1 |
| Switch rating | 16A Resistive 6A Inductive, 100W LED |
| Shortest Switching Time | 15 Minutes |
| Programmable Slots | 48 ON 48 OFF (96 Segments) |
| Permanent ON Facility | Yes (Slider Switch) |
| Cable Capacity (mm2) | 1.5 - 2.5mm2Flexible Cable |
| Cable Entry(s) | Back Entry |

General

| | |
|-----------------------------|-------------------------------|
| Weight (g) | 160 |
| Height (mm) | 92 |
| Width (mm) | 92 |
| Depth (mm) | 60 |
| Body Construction | Polycarbonate |
| Product Colour | White |
| Accessories (Included) | Fittings (Rawl Plugs, Screws) |
| EAN Number | 5012483012291 |
| Guarantee Period | 3 Years |
| Trade Tariff Commodity Code | 9032890090 |

Line Diagrams

