

SLB88

PIR Bulkhead Light

Features & Benefits

- Bulkhead style light with integral PIR detector
- Adjustable light ON times and light level control
- IP44 weatherproof rating
- Uses a standard ES bulb
- Available in black finish



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class I
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Approved Mounting Height (m)	1.8
Motion Detection (m)	8
Detection Angle	110°
Pan & Tilt Adjustment	30° Left/Right From Centre (PIR Only)
LED Type	Bulb Not Included
Mounting Hole Centres (mm)	138 (Diagonal)
Standby Consumption	<1W

Data sheet

SLB88

Light / PIR Bulkheads & Lanterns

Switch rating	30W LED, 500W Halogen, 100W Fluorescent
ON Time Adjustment	5 Seconds to 5 Minutes. User Adjustable
Detection Range (M)	8
Permanent ON Facility	No
Dusk Till Dawn	Yes
Multiple Unit Support	Yes
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	546
Height (mm)	253
Width (mm)	112
Depth (mm)	110
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483007716
Guarantee Period	3 Years
Trade Tariff Commodity Code	9405114090

Line Diagrams

