

STFMMINI

Suretime Mini Flush Mount 360 Degree PIR

Features & Benefits

- Flush mount PIR sensor suited for a wide array of indoor applications
- Manual override (Pulse) for extended light on times.
- Adjustable time ON setting
- Adjustable lux level
- Compact design



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Approved Mounting Height (m)	3
Motion Detection (m)	6 Diameter
Detection Angle	360°
Hole Cut-Out Size (mm)	40
Standby Consumption	<1W
Number Of Channels	1

Switch Rating	200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
LUX Level	10 to 1000
Detection Range (m)	6 Diameter
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 5 Units In Parallel
Cable Entry(s)	Back Entry

General

Weight (g)	51
Height (mm)	73
Width (mm)	50
Depth (mm)	50
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Cover Cover, Screws
EAN Number	5012483014295
Guarantee Period	2 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

