# Data sheet **TGBT6**

## TGBT6

### Boostmaster 2 Hour Plug-In Electronic Boost Timer

#### **Features & Benefits**

- Multiple boost times to choose from.
- Easy to use push button control.
- Boost times illuminated to track the time remaining before switching off.
- ON time can be increased in 4 steps: 0.25, 0.50, 1 and 2 hours.



#### **Technical Data**

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Plug-in
Earth Class Rating	Class I
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Push Buttons	Yes (Boost Button)
Standby Consumption	<1W
Switch rating	13A Resistive, 100W LED, 1000W Halogen, 500W Fluorescent
Shortest Switching Time	15 Minutes
Time Delay Range	15 Miutes to 2 Hours (¼ Hour, ½ Hour, 1 Hour and 2 Hours)
Permanent ON Facility	No



additional information at: https://www.timeguard.com This data was generated on

#### General

Weight (g)	123
Height (mm)	102
Width (mm)	55
Depth (mm)	46
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483011393
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

#### Line Diagrams





