

ZV900B

Automatic Switch Load Controller

Features & Benefits

- Eliminates glow and flicker issues in LED/CFL lamps when used with 2-wire automatic light switches (i.e. Timed, PIR, Photocell automatic switches).
- Under 1W power consumption.
- No additional cabling to the switch required.
- Fits in the ceiling through a 30mm hole.
- Specifically designed to operate with Timeguard ZV700, ZV700B, ZV210, ZV215, DS1N, DS2N, DSSN, DS4, ZV810, ST210 and ST810 when used with LED or CFL lighting.
- The ZV900B is suitable for other companies' 2-wire electronic wall switch products.
- IP20 weatherproof rating.
- Small proportions, but powerful design. Fits in the most confined areas.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface or ceiling hole cut out
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Hole Cut-Out Size (mm)	30
Mounting Hole Centres (mm)	41

Data sheet

ZV900B

Light / Automatic Light Switches

Standby Consumption	<1W
---------------------	-----

General

Weight (g)	15
Height (mm)	45
Width (mm)	28
Depth (mm)	19
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483016008
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536909500

Line Diagrams

