

# ZV900B

## Automatic Switch Load Controller

### Features & Benefits

- Eliminates glow and flicker issues in LED/CFL lamps when used with 2-wire automatic light switches (i.e. Timed, PIR, Photocell automatic switches).
- Under 1W power consumption.
- No additional cabling to the switch required.
- Fits in the ceiling through a 30mm hole.
- Specifically designed to operate with Timeguard ZV700, ZV700B, ZV210, ZV215, DS1N, DS2N, DSSN, DS4, ZV810, ST210 and ST810 when used with LED or CFL lighting.
- The ZV900B is suitable for other companies' 2-wire electronic wall switch products.
- IP20 weatherproof rating.
- Small proportions, but powerful design. Fits in the most confined areas.



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface or ceiling hole cut out
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Hole Cut-Out Size (mm)	30
Mounting Hole Centres (mm)	41

# Data sheet

## ZV900B

Light / Automatic Light Switches

<b>Standby Consumption</b>	<1W
----------------------------	-----

### General

<b>Weight (g)</b>	15
<b>Height (mm)</b>	45
<b>Width (mm)</b>	28
<b>Depth (mm)</b>	19
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	White
<b>EAN Number</b>	5012483016008
<b>Guarantee Period</b>	3 Years
<b>Trade Tariff Commodity Code</b>	8536909500

**Line Diagrams**

